

Amendments to the Claims

1. (Canceled)

2. (Previously Presented) A media pick-up device of a media dispenser,
comprising:

a plurality of conveying rollers rotated by a driving force of a driving
means, for conveying media;

first separating rollers arranged with overlaps to the conveying rollers to
separate the media one by one; and

second separating rollers arranged to face an outer surface of the
conveying rollers with gaps between the second separating rollers and the
conveying rollers, for generating a frictional force to the media;

wherein, in order to maintain intervals between the conveying rollers and
all of the separating rollers, first spacer rollers are mounted on a rotation shaft to
which the conveying rollers are fixed, and second spacer rollers corresponding to
the first spacer rollers are mounted on a shaft to which the first and second
separating rollers are fixed.

3. (Canceled)

4. (Canceled)

5. (Previously Presented) A media pick-up device of a media dispenser, comprising:

a plurality of conveying rollers rotated by a driving force of a driving means, for conveying media;

first separating rollers arranged with overlaps to the conveying rollers to separate the media one by one; and

second separating rollers arranged to face an outer surface of the conveying rollers with gaps between the second separating rollers and the conveying rollers, for generating a frictional force to the media;

wherein the conveying rollers comprise first conveying rollers arranged with overlaps to the first separating rollers, and second conveying rollers arranged to face the second separating rollers with gaps between the second separating rollers and the second conveying rollers; and

wherein the second separating rollers are arranged between the first separating rollers.

6. (Previously Presented) A media pick-up device of a media dispenser, comprising:

a plurality of conveying rollers rotated by a driving force of a driving means, for conveying media;

first separating rollers arranged with overlaps to the conveying rollers to separate the media one by one; and

second separating rollers arranged to face an outer surface of the conveying rollers with gaps between the second separating rollers and the conveying rollers, for generating a frictional force to the media;

wherein a torsion spring for providing an elastic force to push the first and second separating rollers to the conveying rollers is installed on a shaft to which the first and second separating rollers are fixed.

7. (Original) The media pick-up device of claim 6, wherein the torsion spring comprises a plate spring fixed between a bracket rotatably supported on the shaft and a main body.

8-9. (Cancelled)

10. (Previously Presented) A media pick-up device of a media dispenser, comprising:

a plurality of conveying rollers rotated by a driving force of a driving means, for conveying media;

first separating rollers arranged with overlaps to the conveying rollers to separate the media one by one; and

second separating rollers arranged to face an outer surface of the conveying rollers with gaps between the second separating rollers and the conveying rollers, for generating a frictional force to the media;

wherein both the first and second separating rollers are mounted on a same shaft.

11-20 (Canceled)